Bottom Box Truss Capacities - (PLF)														
Category		Light				Medium					Heavy		Extra Heavy	
Model Series		C-0350	C-0450	C-0550	C-0650	C-0480	C-0580	C-0680	C-0780	C-0880	C-07110	C-08110	C-08140	C-10140
Inside Width - (FT)		3	4	5	6	4	5	6	7	8	7	8	8	10
Free Span - (FT)	30	300	220	220	220									
	40	230	200	160	160	500	400	380	350	250				
	50	175	175	125	125	400	315	300	300	250				
	60					325	250	250	250	240				
	70					230	175	175	175	175	295	295		
	80					175	125	125	125	125	235	235		
	90	أأنأنأ	ينتشنن	فتختف							185	185		
	100										150	150	345	275
	110	أأأأأأ	فنفف				أخنفا				125	125	280	230
	120												235	190
	130												190	155
	140												155	125

- Designed in accordance with AISC Manual of Steel Construction, IBC, & ASCE standards.
- Constructed with ASTM A529-50 Grade 50 mill certified structural steel angle.
- Hot dipped galvanized, painted, powder coated, and GalvXtra rustic brown finishes available.
- Welded and factory assembled options are available.
- Full OSHA compliance.
- Custom widths and spans also available.
- Designed to meet all international building codes.
- Manufactured & containerized for exports.



